

Freezers

Range brochure

Horizontal, vertical, double-door and countertop freezing for retail and foodservice.

Frozen storage and display built for kitchens and shop floors that treat equipment hard - heavier gaskets, reinforced hinges and defrost cycles timed around service rather than a fixed clock.

AT A GLANCE

- 100-600 L gross capacity
- Down to -24 °C hold temperature
- Horizontal, vertical and countertop formats

MODELS IN THIS RANGE (7)

Model	Code	Capacity	Doors	Energy	kWh/year
Chest Freezer 200	EFC-200	200 L	1	A	318
Chest Freezer 300	EFC-300	300 L	1	A	396
Chest Freezer 420	EFC-420	420 L	1	B	512
Upright Freezer 350	EFU-350	350 L	1	B	584
Upright Freezer 550	EFU-550	550 L	2	C	892
Glass Top Freezer 600	EFG-600	600 L	2	C	1042
Countertop Freezer 100	EFT-100	100 L	1	B	438

Chest Freezer 200 - EFC-200

Freezers - Model detail

200 L chest freezer with a solid lid and manual defrost.

KEY SPECIFICATION

Gross capacity	200 L
Net capacity	190 L
Doors	1
Dimensions (W x D x H)	940 x 620 x 860 mm
Net weight	46 kg
Energy class	A
Annual energy consumption	318 kWh/year
Refrigerant	R290
Temperature range	-24 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Lowest consumption per litre

A solid lid and 60 mm insulation beat any glass-top format on running cost.

- Holds through a power cut

Rated to hold below -18 °C for 28 hours unpowered when full - relevant in markets with unreliable supply.

- Drain plug and basket

Front drain and coated baskets make manual defrost a ten-minute job, not an afternoon.

Chest Freezer 300 - EFC-300

Freezers - Model detail

300 L chest freezer with a digital controller and three baskets.

KEY SPECIFICATION

Gross capacity	300 L
Net capacity	286 L
Doors	1
Dimensions (W x D x H)	1120 x 680 x 860 mm
Net weight	58 kg
Energy class	A
Annual energy consumption	396 kWh/year
Refrigerant	R290
Temperature range	-24 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Lockable set point

The controller can be locked so staff cannot raise the temperature to speed up access.

- Three-basket rotation

Baskets keep first-in-first-out workable in a deep cabinet, which is where frozen stock usually goes wrong.

- Counterbalanced lid

Stays open at any angle, so loading does not need a second pair of hands.

Chest Freezer 420 - EFC-420

Freezers - Model detail

420 L chest freezer for depot and central-kitchen storage.

KEY SPECIFICATION

Gross capacity	420 L
Net capacity	402 L
Doors	1
Dimensions (W x D x H)	1420 x 720 x 890 mm
Net weight	76 kg
Energy class	B
Annual energy consumption	512 kWh/year
Refrigerant	R290
Temperature range	-24 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Case-quantity storage

Internal dimensions take standard frozen cases without stacking them on edge.

- 80 mm insulation

Thicker walls hold temperature longer and cut consumption per litre at this size.

- Braked castors

Moves for cleaning without emptying, which is a real constraint in a central kitchen.

Upright Freezer 350 - EFU-350

Freezers - Model detail

350 L upright freezer with five drawers and no-frost operation.

KEY SPECIFICATION

Gross capacity	350 L
Net capacity	322 L
Doors	1
Dimensions (W x D x H)	670 x 700 x 1900 mm
Net weight	88 kg
Energy class	B
Annual energy consumption	584 kWh/year
Refrigerant	R290
Temperature range	-24 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Floor area of a chest half its size

670 mm wide, so 350 L of frozen storage fits a kitchen where a chest would not.

- No-frost operation

Automatic defrost removes the manual cycle, and with it the temperature excursion that comes with it.

- Visible stock

Drawers rather than a deep well, so what is at the back is still findable.

Upright Freezer 550 - EFU-550

Freezers - Model detail

550 L twin-door upright freezer for service kitchens.

KEY SPECIFICATION

Gross capacity	550 L
Net capacity	508 L
Doors	2
Dimensions (W x D x H)	1340 x 720 x 1980 mm
Net weight	148 kg
Energy class	C
Annual energy consumption	892 kWh/year
Refrigerant	R290
Temperature range	-24 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Independently sealed halves

Opening one door leaves the other half at temperature, which matters during a rush.

- Commercial hinge set

Rated for continuous service-kitchen duty rather than domestic cycling.

- Stainless interior

Wipe-down interior that survives kitchen cleaning chemicals and food-safety audits.

Glass Top Freezer 600 - EFG-600

Freezers - Model detail

600 L glass-top freezer for frozen display in retail aisles.

KEY SPECIFICATION

Gross capacity	600 L
Net capacity	572 L
Doors	2
Dimensions (W x D x H)	1860 x 720 x 890 mm
Net weight	164 kg
Energy class	C
Annual energy consumption	1042 kWh/year
Refrigerant	R290
Temperature range	-22 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Heated sliding glass

Perimeter heating keeps the glass clear at 65% relative humidity, so product stays visible.

- LED perimeter

Lights the pack face rather than the freezer well, which is what actually drives frozen impulse.

- Retail-height well

890 mm to the glass, so product is reachable by a shopper without leaning into the cabinet.

Countertop Freezer 100 - EFT-100

Freezers - Model detail

100 L glass-door countertop freezer for ice cream and frozen impulse at the till.

KEY SPECIFICATION

Gross capacity	100 L
Net capacity	88 L
Doors	1
Dimensions (W x D x H)	540 x 560 x 900 mm
Net weight	46 kg
Energy class	B
Annual energy consumption	438 kWh/year
Refrigerant	R290
Temperature range	-22 to -18 C
Power supply	220-240 V / 50 Hz

FEATURES

- Frozen impulse at the till

A 540 mm footprint puts frozen product where the purchase decision is made.

- Fog-free glass

Heated low-E glazing stays clear at 65% relative humidity.

- Deep-frozen hold

Holds -22 °C, the hard ice cream needs to keep its texture.